

TIJ1800-Mini Thermal InkJet



ADVANTAGES

1. Compact-sized:

Compact sized and with 4.3-inch touchscreen which provides an enhanced user interface.

2. Friendly UI and Interactive Design:

Simple and easy user interface for easy operation.

3. Automatic ink Identification:

Automatically identifies and selects the proper firing for the best print quality.



Specifications

General

Display	4.3 Touch color LCD with back light.
Languages	Arabic, English, Spanish, Portuguese, Russian, Turkish, and Chinese.
Electrical Requirements	AC 100 V~240, 50/60HZ
Mounting Orientation	Horizontal or Downside
Operating Temperature	15°C – 45°C

Optional Accessories

Encoder	Provide high print quality on unstable encoder
Photocell	Provide more reliable and precise sensing parameter
Alarm Kit	Alert users in the event of an incident

Cartridge

Ink	Solvent Base or water-base cartridges
Print Distance	1-5 mm recommended print distance
Print Height	Up to 6 lines and limited to 12.7mm (0.5")
Resolution	(50-900) dpi speed up to (0.1-500m/min)
Print Capability	Alphanumeric, logos, date/time, counter, shift code

Eggs Coding



Food Industry



Beverage Industry



Cosmetics



Electronic



Cables & Pipes



Medical Industry



Building Materials



Email: info@magicprint-int.com

phone: 010/50307844 - 011/03893060 - 010/17900929 - 010/08835133

الإدارة 1: عمارة 4 مساكن جامعة القاهرة الدور الاول شقة 3 الجيزة
الإدارة 2: عمارة 35 بلوك 16087 المنطقة الإدارية - الحى الخامس - مدينة العبور الدور الثالث